

- Adjustable speed temperature
- LED display
- Multi-function for either hot or cold laminating
- Separate operating buttons for forward, reverse and stop auto-matic memory function
- Adjust to various paper thicknesses
- Tension Adjustment Unit
- New LED display detects missing safety guard
- Perforated wheel to easily allow manual burst and separation
- Automatically bursts/separates after single sided lamination, saving time and labor.
- Complete with stand & casters
- New improved auto-feed mechanism
- 1 speed adjuster's, making setting speed & overlap easy
- Can easily set machine for single sided thermal lamination



#### Optional Extras

DHBURST - Burst and Separation Unit



#### Warranty

12 Months Parts Only



Australian RCM certified

# DH360AF1

## HOT ROLL LAMINATOR



### Technical Specifications:

Product Code & Model Name:

Max. working temperature:

Laminating Speed:

Heating method:

Maximum Laminating Width:

Maximum Mounting Thickness:

Rollers:

Recommended film thickness:

Core size of mandrel:

Power Supply:

Power Consumption:

Assembled Dimensions:

Machine Shipping Dimensions (mm):

Machine Shipping Weight (kg)

**DH360AF1** - Hot Roll laminator

Up to 140°C

Variable Speed (up to 1.6m per min)

Inside Infrared heating

340mm (13")

Opens up to 5mm

2 Heating silicon rollers (Φ44mm)

2 Cold silicon rollers (Φ 30mm)

Up to 250 microns

76mm (3")

AC100 – 240V/50,60Hz

(Standard 10 AMP plug)

700w

1052(L) x 569(W) x 633(H)

900(L) x 750(W) x 910(H)

104kg



For additional information on this product please use the above QR Code.

All images are for illustration purposes only please contact your nearest dealer for further assistance.

**Please Note:** All shipping dimensions & weights are subject to change without notice.