

ECO330

POUCH LAMINATOR



- Dual Heating System (hot roll with hot plate)
- All metal heavy duty construction
- Variable temperature control
- Laminates both hot and cold
- Suitable for hot foiling and mounting
- Bubble free photo lamination
- Overheat protection mode
- Power and ready light indicator
- Auto shut off function/ECO mode function
- Forced shut off
- Auto fault alert
- Anti-Jam reverse mode
- ECO mode Phase 1 reduces the temperature to 80° C for energy saving after a period of approximately 30 minutes
- ECO mode Phase 2 automatically shuts off the machine after a period of 60 minutes
- Auto switch off, enables the operator to leave without waiting for the machine to cool down. Just press and hold the heat button for 3 seconds when the roller temperature reaches 80° C, the machine will automatically switch off.
- Auto fault alert displays the fault type and then shuts off the machine for safety. Please refer to machine operation manual.

Technical Specifications:

Product Code & Model Name:	ECO330 – Pouch Machine 330mm
Dual Heating System:	Up to 160° C
Laminating Speed:	0.65m/min
Maximum Laminating Width:	≤ 330mm
Maximum Laminating Thickness:	Up to 1mm
Laminating Film Thickness:	Up to 250 microns
Power Consumption:	650W



Warranty

12 Months Parts Only



Australian RCM Certified



Standard 10amp power
AC 110V/220V (50/60Hz)

ALC

www.alclaminating.com
Australian Laminating Company

Pty Ltd

These images are for illustration purposes only please contact your nearest dealer for further assistance.

Please Note: All shipping dimensions & weights are subject to change.

Version 1.2