


**Product Information**

Construction: Polymeric PVC  
 Main Application: Protection against abrasion, moisture, UV and constant surface contact.  
 Shelf life: Up to 1 Year  
 Storage Conditions: Stored up to 21°C and 50% relative humidity.  
 Adhesive: Pressure sensitive solvent based acrylic (Permanent)  
 Adhesive Colour: Grey, Clear  
 Colour: White  
 Finish: Gloss  
 Core: 76mm

Printer Compatibility: This material is suited for solvent, latex and UV printers.

**Durability**

 Up to 5 years\*

**Thickness**

PVC Film Thickness: 110 ± microns  
 Adhesive Thickness: 25 ± microns  
 Total Thickness: 135 ± microns  
 Liner Thickness: 120 ± gsm double sided PE coated paper

**Standard Stock Sizes**

Codes	Standard sizes	Core	Adhesive
Gloss			
S77	1370mm x 50m	76mm	Clear Permanent
S79	1370mm x 50m	76mm	Grey Permanent

\* Outdoor life will vary depending on installation technique, location and relative position to the sun.

V1.0

**PLEASE NOTE** – All information, recommendations and suggestions contained herein, without limitation, stated values (collectively the “information”) shall be used only as a guide by Purchaser and not for specification or any other purpose. The information does not constitute a warranty or guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. The seller shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser’s reliance on the information.



[www.alclaminating.com](http://www.alclaminating.com)

**Australian Laminating Company**

Pty Ltd

76 NORTH VIEW DRIVE  
 SUNSHINE WEST VIC 3020

P: +61 (0)3 9312 7400  
 F: +61 (0)3 9312 7455  
 SALES@ALCLAMINATING.COM