


Product Information

Construction:	PET (Polyester), Acid Free
Main Application:	Protection against abrasion, moisture, UV and constant surface contact.
Shelf Life:	Up to 2 years
Storage Conditions:	Stored up to 25°C and up to 50% relative humidity in original packaging
Adhesive:	26 ± microns pressure sensitive solvent based acrylic (Clear Permanent)
Features:	Ideal for ink repellent application
Finish:	Gloss
Core:	76mm
Laminating Curing Time:	Once the laminating is completed, it is recommended to lay the laminated print flat for 24 hours to allow the proper adhesive curing time prior to trimming

Durability



Up to 3 years*

Thickness

Film Thickness:	36 ± microns
Adhesive Thickness:	26 ± microns
Total Thickness:	62 ± microns
Liner Thickness:	80 gsm single sided PE coated paper

Standard Stock Sizes

Codes	Standard sizes	Core	Adhesive
Gloss			
L162	1370mm x 50m	76mm	Clear Permanent
L166	1520mm x 50m	76mm	Clear Permanent

* Outdoor life will vary depending on installation technique, location and relative position to the sun.

PLEASE NOTE – All information, recommendations and suggestions contained herein, without limitation, stated values (collectively the “information”) shall be used only as a guide by Purchaser and not for specification or any other purpose. The information does not constitute a warranty or guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. The seller shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser’s reliance on the information.

V1.1

ALC

www.alclaminating.com

Australian Laminating Company

Pty Ltd

76 NORTH VIEW DRIVE
SUNSHINE WEST VIC 3020

P: +61 (0)3 9312 7400
F: +61 (0)3 9312 7455
SALES@ALCLAMINATING.COM