


## Product Information

Construction:	Monomeric Vinyl SAV
Main Application:	Protection against abrasion, moisture, UV and constant surface contact.
Shelf Life:	Up to 2 years
Storage Conditions:	Stored up to 25°C and up to 50% relative humidity, in original packaging.
Adhesive:	25 ± microns pressure sensitive solvent based acrylic (Clear permanent) – Bubble Free “High Tack”
Finish:	Matt
Colour:	White
Core:	76mm

Printer Compatibility: This material is suited for solvent, latex and UV printers

## Durability

 Up to 3 years\*

## Thickness

PVC Vinyl Thickness:	150 ± microns
Adhesive Thickness:	25 ± microns
Total Thickness:	175 ± microns
Liner Thickness:	140 gsm double sided PE coated paper

## Standard Stock Sizes

Codes	Standard sizes	Core	Adhesive
Matt			
HT44	1370mm x 50m	76mm	Clear Bubble Free Permanent

\* Outdoor life will vary depending on installation technique, location and relative position to the sun.

V1.2

**PLEASE NOTE** – All information, recommendations and suggestions contained herein, without limitation, stated values (collectively the “information”) shall be used only as a guide by Purchaser and not for specification or any other purpose. The information does not constitute a warranty or guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. The seller shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser’s reliance on the information.

# ALC

[www.alclaminating.com](http://www.alclaminating.com)

**Australian Laminating Company**

Pty Ltd

76 NORTH VIEW DRIVE  
SUNSHINE WEST VIC 3020

P: +61 (0)3 9312 7400  
F: +61 (0)3 9312 7455  
SALES@ALCLAMINATING.COM