


This is a premium monomeric UV cold lamination film with a range of different face films for over laminating digitally printed inkjet prints for medium term outdoor UV stability.

Product Information

Construction:	Monomeric PVC, Acid free
Main Application:	Protection against abrasion, moisture, UV and constant surface contact.
Shelf Life:	Up to 2 years
Storage Conditions:	Stored up to 25°C and up to 50% relative humidity in original packaging.
Adhesive:	25 ± microns pressure sensitive solvent based acrylic (Clear Permanent)
Features:	Low shrinkage
Finishes:	Gloss & Satin
Core:	76mm

Durability



Up to 3 years*

Laminating Temperature: Cold or heat assist up to 50°C

Lamination Curing Time: Once the lamination is completed, it is recommended to lay the laminated print flat for 24 hours to allow the proper adhesive curing time prior to trimming.

Thickness

PVC Film Thickness:	80 ± microns
Adhesive Thickness:	25 ± microns
Total film Thickness:	105 ± microns
Liner Thickness:	80 gsm single sided PE coated paper

Standard Stock Sizes

Codes		Standard sizes	Core	Adhesive
Gloss L084	Satin L074	1530mm x 50m	76mm	Clear Permanent

* OUTDOOR LIFE – Will vary depending on installation technique, location and relative position to the sun.

V1.2

PLEASE NOTE – All information, recommendations and suggestions contained herein, without limitation, stated values (collectively the “information”) shall be used only as a guide by Purchaser and not for specification or any other purpose. The information does not constitute a warranty or guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. The seller shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser’s reliance on the information.

ALC

www.alclaminating.com

Australian Laminating Company

Pty Ltd

76 NORTH VIEW DRIVE
SUNSHINE WEST VIC 3020

P: +61 (0)3 9312 7400
F: +61 (0)3 9312 7455
SALES@ALCLAMINATING.COM