

## Product Information

Construction:	Biaxial Orientated Polypropylene
Usage:	Thermal laminating digital prints
Main Application:	Single sided or double sided application; Easy application; Protects against abrasion, moisture and constant surface contact.
Storage Conditions:	Stored up to 25°C, 50% relative humidity, in original packing of the box.
Adhesive:	Thermal Activated EVA Adhesive
Finish:	Gloss
Core:	3" (76mm )

Lamination Curing Time: Once the lamination is completed, it is recommended to lay the laminated print flat for 24 hours to allow the proper adhesive curing time prior to trimming.

## Thickness

	Gloss
Base Thickness:	15 ± microns
Adhesive Thickness:	20 ± microns
Total Thickness:	35 ± microns

## Standard Stock Sizes

Codes	Standard sizes	Core	Adhesive
Gloss X07	445mm x 2000m	76mm	Thermal Activated EVA

\* Outdoor life will vary depending on installation technique, location and relative position to the sun.

V1.2

**PLEASE NOTE** – All information, recommendations and suggestions contained herein, without limitation, stated values (collectively the “information”) shall be used only as a guide by Purchaser and not for specification or any other purpose. The information does not constitute a warranty or guaranty of any type whatsoever. Purchaser should independently determine the suitability of all material purchased and must confirm adaptability and other characteristics by conducting its own tests. The seller shall have no liability as a result of any loss, expense, damage, cost or other injury which results from Purchaser’s reliance on the information.

# ALC

[www.alclaminating.com](http://www.alclaminating.com)

**Australian Laminating Company**

Pty Ltd

76 NORTH VIEW DRIVE  
SUNSHINE WEST VIC 3020

P: +61 (0)3 9312 7400  
F: +61 (0)3 9312 7455  
SALES@ALCLAMINATING.COM